according to 1907/2006/EC, Article 31




Revision: 24.02.2021

Printing date 24.02.2021

Version number 38

SECTION 1: Identification of the substance/mixture and of the company/



(Contd. on page 2)

GB

according to 1907/2006/EC, Article 31



Revision: 24.02.2021

# Printing date 24.02.2021

Version number 38

#### Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 1) H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. P280 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

#### 2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	<15%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226;  STOT SE 3, H336	2.5-<10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; (\$ Asp. Tox. 1, H304; (\$ STOT SE 3, H336	2.5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226;  Asp. Tox. 1, H304; Aquatic Chronic 2, H411;  STOT SE 3, H335- H336	1-<2.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidyl sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	<i>≥</i> 0.1-<0.25%

#### SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 24.02.2021

Version number 38

Professional Coating Systems

Revision: 24.02.2021

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 2)

· After skin contact:

Generally the product does not irritate the skin. Immediately rinse with water.

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Printing date 24.02.2021

Version number 38



Revision: 24.02.2021

Trade name: Mipa PU 250-30 2K-PU-Lack

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

# SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

#### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

#### 112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m<sup>3</sup>, 50 ppm Long-term value: 133 mg/m<sup>3</sup>, 20 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

• **Respiratory protection:** Not required.



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB

# Safety data sheet according to 1907/2006/EC, Article 31



Printing date 24.02.2021

Version number 38

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 4)

· Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemi	cal properties
• 9.1 Information on basic physical and o • General Information • Appearance:	chemical properties
Form: Colour: Odour: Odour threshold:	Fluid According to product specification Characteristic Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition Melting point/freezing point: Initial boiling point and boiling range</li> </ul>	Undetermined. : 124 °C
· Flash point:	30 °C (DIN 53213)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	315 °C (DIN 51794)
<ul> <li>Decomposition temperature:</li> </ul>	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	1.2 Vol % 7.5 Vol %
· Vapour pressure at 20 °C:	<15 hPa
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	1.403 g/cm <sup>3</sup> (DIN 53217) Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic at 20 °C:</li> </ul>	Not determined. 200-220 s (ISO 6 mm)
· Solvent content: VOC (EC)	25.74 %
Solids content (weight-%):	74.3 %
	(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Printing date 24.02.2021

#### Version number 38

Professional Goating Systems

Revision: 24.02.2021

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 5)

<sup>•</sup> 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

## SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 64742-95-6 Hydrocarbons, C9, aromatics

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Additional toxicological information:

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### · 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Harmful to aquatic organisms

(Contd. on page 7)

according to 1907/2006/EC, Article 31



(Contd. of page 6)

Printing date 24.02.2021

#### Version number 38

Trade name: Mipa PU 250-30 2K-PU-Lack

· 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	UN1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es)		
ADR		
Class	3 (F1) Flammable liquids.	
Label	3	
IMDG, IATA		
•		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG, IATA	<i>III</i>	
14.5 Environmental hazards: Marine pollutant:	No	
•		
14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler of		
EMS Number: Stowage Category	F-E, <u>S-E</u> A	

according to 1907/2006/EC, Article 31



Revision: 24.02.2021

Printing date 24.02.2021

Version number 38

Trade name: Mipa PU 250-30 2K-PU-Lack

	(Contd. of page 7)
<ul> <li>14.7 Transport in bulk according to Annex I of Marpol and the IBC Code</li> </ul>	II Not applicable.
· Transport/Additional information:	
• ADR • Transport category • Tunnel restriction code • Remarks:	3 D/E ≤ 450 l: -
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Remarks:</li> </ul>	5L ≤ 30 l: -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

# SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)

GB

# Safety data sheet according to 1907/2006/EC, Article 31



Revision: 24.02.2021

# Printing date 24.02.2021

Version number 38

# Trade name: Mipa PU 250-30 2K-PU-Lack

(Co	ontd. of page 8)
· Classification according to Regulation (EC) No 1272/2008	
The classification of the mixture is generally based on the calculation method using sub according to Regulation (EC) No 1272/2008.	ostance data
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fe Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)	er (Regulations
ICAO: International Civil Aviation Organisation	
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (Éuropean Agreement International Carriage of Dangerous Goods by Road)	concerning the
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Sens. 1: Skin sensitisation – Čategory 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	
	GB -