Professional Coating Systems

Printing date 08.05.2019

Version number 9

Revision: 30.05.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

- Trade name: 1K-Primer N 45
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
1.4 Emergency telephone number: +49(0)700 24112112 (MIP)

# **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

×

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



*Eye Irrit.* 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

• Hazard-determini n-Butyl acetate	ng components of labelling:
ethyl acetate	
butan-1-ol	
· Hazard statements	
H225 Highly flam	nable liquid and vapour.
H319 Causes serio	pus eye irritation.
H336 May cause d	rowsiness or dizziness.
· Precautionary stat	tements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

(Contd. on page 2)

GB

according to 1907/2006/EC, Article 31 Version number 9



Revision: 30.05.2018

# Trade name: 1K-Primer N 45

Printing date 08.05.2019

	(Contd. of page 1)
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	3 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional inform	ation:
EUH066 Repeated	exposure may cause skin dryness or cracking.
· 2.3 Other hazards	
· Results of PBT an	d vPvB assessment
DDT. Not applicat	

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

n-Butyl acetate Flam. Liq. 3, H226;  STOT SE 3, H336	10-25%
ethyl acetate	10-25%
Nitrocellulose, nitrogen content <12,6%	2.5-<10%
butan-1-ol	≥1-<2.5%
	<ul> <li>Flam. Liq. 3, H226;  STOT SE 3, H336</li> <li>ethyl acetate</li> <li>Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336</li> <li>Nitrocellulose, nitrogen content &lt;12,6%</li> <li>Expl. 1.1, H201</li> <li>butan-1-ol</li> <li>Flam. Liq. 3, H226;  Eye Dam. 1, H318;  Acute Tox. 4,</li> </ul>

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

1

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.05.2019

Version number 9

Professional Coating Systems

Revision: 30.05.2018

Trade name: 1K-Primer N 45

• Information for doctor:

(Contd. of page 2)

**SECTION 5: Firefighting measures** 

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

# **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
  6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

# SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31



Revision: 30.05.2018

Printing date 08.05.2019

Version number 9

Trade name: 1K-Primer N 45

(Contd. of page 3)

# 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace:

#### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

# 141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

#### 71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

# SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:
- Form: Colour:

Fluid According to product specification

(Contd. on page 5)



Revision: 30.05.2018

Printing date 08.05.2019

Version number 9

Trade	name:	1K-Primer	N 45

	(Contd. of page
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 77 °C
Flash point:	-4 °C (DIN EN ISO 1523:2002)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air
	vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 •C:	97 hPa
Density at 20 °C:	1.382 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	140 s (DIN 53211/4)
Solvent content:	
VOC (EC)	40.91 %
Solids content (weight-%):	59.1 %
9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

2

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31



Revision: 30.05.2018

\_\_\_\_\_

Printing date 08.05.2019

Version number 9

Trade name: 1K-Primer N 45

(Contd. of page 5)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- $\cdot$  Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### · 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper ship · ADR · IMDG, IATA	ing name UN1263 PAINT PAINT

(Contd. on page 7)

GB -



Revision: 30.05.2018

Printing date 08.05.2019

Version number 9

Trade name: 1K-Primer N 45

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
• EMS Number:	<i>F-E,<u>S-E</u></i>
· Stowage Category	В
• 14.7 Transport in bulk according to Annex II	
Marpol and the IBC Code	Not applicable.
• Transport/Additional information:	
· ADR	
· Transport category	2
• Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· UN ''Model Regulation'':	UN 1263 PAINT, 3, II

# **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

\*

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

Class Share in % NK 25-50

(Contd. on page 8)

GB

Professional Coating Systems

Revision: 30.05.2018

Printing date 08.05.2019

Version number 9

Trade name: 1K-Primer N 45

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 7)

#### **SECTION 16: Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Relevant phrases H201 Explosive; mass explosion hazard. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives - Division 1.1 Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • \* Data compared to the previous version altered.