according to 1907/2006/EC, Article 31 Version number 8



Revision: 08.08.2018

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## · 1.1 Product identifier

Printing date 23.04.2019

- · Trade name: 2K-HS-Klarlack CC9
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Clear coating material, Varnish
- 1.3 Details of the supplier of the safety data sheet
  Manufacturer/Supplier: MIPA SE
  Am Oberen Moos 1
  D-84051 Essenbach
  Tel.: +49(0)8703-922-0
  Fax.: +49(0)8703-922-100
  e-mail: sdb-registratur@mipa-paints.com
  www.mipa-paints.com
  1.4 Emergency telephone number: +49(0)700 24112112 (MIP)

# **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Sens. 1H317 May cause an allergic skin reaction.STOT SE 3H336 May cause drowsiness or dizziness.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- *The product is classified and labelled according to the CLP regulation. Hazard pictograms*



### · Signal word Warning

• Hazard-determining components of labelling: n-Butyl acetate 2-ethoxy-1-methylethyl acetate Reaction mass of pentamethyl-piperidyl sebacate

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31



Revision: 08.08.2018

Printing date 23.04.2019

Version number 8

Trade name: 2K-HS-Klarlack CC9

	(Contd. of page 1)
Pentaerythritol	tetrakis(3-mercaptopropionate)
· Hazard statem	ents
H226 Flammal	ble liquid and vapour.
H317 May cau	se an allergic skin reaction.
H336 May cau	se drowsiness or dizziness.
H411 Toxic to	aquatic life with long lasting effects.
· Precautionary	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P	2353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional info	ormation:
•	ited exposure may cause skin dryness or cracking.
· 2.3 Other haza	
· Results of PBT	and vPvB assessment
• <b>PBT:</b> Not appl	

• *PBT*: Not applicable. • *vPvB*: Not applicable.

2

# SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; () STOT SE 3, H336	10-25%
CAS: 110-12-3 EINECS: 203-737-8 Reg.nr.: 01-2119472300-51	5-methylhexan-2-one Flam. Liq. 3, H226; (1) Acute Tox. 4, H332	2.5-<10%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate Flam. Liq. 3, H226;  STOT SE 3, H336	2.5-<10%
CAS: 127519-17-9 ELINCS: 407-000-3 Reg.nr.: 01-0000015648-61	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H- benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl] propionates Aquatic Chronic 2, H411	≥0.25-<2.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidyl sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; () Skin Sens. 1A, H317	≥0.25-<1%

according to 1907/2006/EC, Article 31



Revision: 08.08.2018

Printing date 23.04.2019

Version number 8

Trade name: 2K-HS-Klarlack CC9

		(Contd. of page 2)
CAS: 7575-23-7	Pentaerythritol tetrakis(3-mercaptopropionate)	≥0.25-<1%
EINECS: 231-472-8	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🚸 Acute	
Reg.nr.: 01-2119486981-23	Ťox. 4, H302; Skin Sens. 1A, Ĥ317	
CAS: 77-58-7	dibutyltin dilaurate	≥0.1-<0.25%
EINECS: 201-039-8	<b>W</b> uta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370;	
Reg.nr.: 01-2119496068-27	STOT RE 1, H372; < Skin Corr. 1C, H314; Eye Dam. 1, H318;	
	🚯 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ( Skin	
	Sens. 1, H317	
. Additional information · For	r the wording of the listed hazard phrases refer to section 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.
- Information for doctor:

# **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

• For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

# **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Revision: 08.08.2018

Printing date 23.04.2019

Version number 8

Trade name: 2K-HS-Klarlack CC9

(Contd. of page 3)

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m<sup>3</sup>, 100 ppm Long-term value: 95 mg/m<sup>3</sup>, 20 ppm Sk

#### 77-58-7 dibutyltin dilaurate

WEL Short-term value: 0.2 mg/m<sup>3</sup> Long-term value: 0.1 mg/m<sup>3</sup>

as Sn; Sk

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:
- Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves (EN 374)

• **Material of gloves** Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.7$  mm

· **Breakthrough time of glove material** Value for the permeation: Level  $\leq 3$ 

# Safety data sheet according to 1907/2006/EC, Article 31



Revision: 08.08.2018

(Contd. of page 4)

Printing date 23.04.2019

· Eye protection:

Version number 8

Trade name: 2K-HS-Klarlack CC9



Tightly sealed goggles

#### **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Colour: According to product specification · Odour: *Characteristic* · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 124 °C · Flash point: 27 °C (DIN EN ISO 1523:2002) · Flammability (solid, gas): Not applicable. · Ignition temperature: 370 °C (DIN 51794) · Decomposition temperature: Not determined. • Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive air/ · Explosive properties: vapour mixtures are possible. · Explosion limits: 1.2 Vol % Lower: 7.5 Vol % Upper: 10.7 hPa • Vapour pressure at 20 °C: • Density at 20 •C: 1.004 g/cm<sup>3</sup> (DIN EN ISO 2811-1) · Relative density Not determined. Not determined. · Vapour density Not determined. · Evaporation rate · Solubility in / Miscibility with Not miscible or difficult to mix. water: Not determined. · Partition coefficient: n-octanol/water: · Viscosity: Dynamic: Not determined. Kinematic at 20 °C: 33 s (DIN 53211/4) · Solvent content: 39.29 % VOC (EC) 60.7 % Solids content (weight-%): • 9.2 Other information No further relevant information available.

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31



Revision: 08.08.2018

Printing date 23.04.2019

Version number 8

Trade name: 2K-HS-Klarlack CC9

(Contd. of page 5)

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- $\cdot$  10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

# **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

7575-23-7 Pentaerythritol tetrakis(3-mercaptopropionate)

Oral LD50 1,000-2,000 mg/kg (rat)

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot$  **Reproductive toxicity** Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 3 (German Regulation) : extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- Harmful to aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

\*

Safety data sheet according to 1907/2006/EC, Article 31 Professional Coating Systems

Revision: 08.08.2018

Printing date 23.04.2019

Version number 8

Trade name: 2K-HS-Klarlack CC9

(Contd. of page 6)

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation


Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.



GB

according to 1907/2006/EC, Article 31



Revision: 08.08.2018

Printing date 23.04.2019

Version number 8

Trade name: 2K-HS-Klarlack CC9

	(Contd. of page 7
· Danger code (Kemler):	30
· EMS Number:	<i>F-E,<u>S-E</u></i>
· Stowage Category	A
· 14.7 Transport in bulk according to A	nnex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
$\cdot$ Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, 111, ENVIRONMENTALLY HAZARDOUS

# SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20

· Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate

Annex I Part 1

· National regulations:

Class	Share in %
NK	25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- *H400 Very toxic to aquatic life.*

(Contd. on page 9)

<sup>-</sup> GB

Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article 31 Version number 8



Revision: 08.08.2018

Trade name: 2K-HS-Klarlack CC9

Printing date 23.04.2019

(Contd. of page 8) H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. · Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1C: Skin corrosion/irritation – Category 1C Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Muta. 2: Germ cell mutagenicity – Category 2 Repr. 1B: Reproductive toxicity - Category 1B STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 • \* Data compared to the previous version altered.