










Intended use

Mipa Silikonentferner is a CHC-free cleaning and degreasing agent for all metallic and polymeric materials. It can be applied by paintbrush, brush, wipe, sponge or by spraying.

Spreading rate: --

Processing instructions

	Colour colourless					
	Mixing ratio					
	Hardener		by weight (lacquer : hardener)	by volume (lacquer : hardener)		
	--	--	--	--		
	Hardener					
	for complete paintwork			for partial paintwork		
	--	--	--	--		
	Pot life					
	--					
	Thinner					
	--					
	Spray viscosity					
	gravity spray gun			Airmix/Airless		
	--	--	--	--		
	Application mode					
	Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
	--	--	--	--	--	--
	Flash-off time					
	--					
	Dry coat thickness					
	--					
	Drying time					
	object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
	--	--	--	--	--	--

Version: en 1120

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com

Note

- Storage:** at least 3 years in unopened original containers.
- VOC Regulation :** EU limit value for this product (category B/a): 850 g/l
This product contains max. 743 g/l of VOC.
- Processing conditions:** from +10 °C and up to 80 % relative humidity. Ensure adequate air ventilation.
- Processing instructions:** –