










Intended use

Mipa Silikonentferner is a CHC-free cleaning and degreasing agent for all metallic and polymeric materials. It can be applied by paintbrush, brush, wipe, sponge or by spraying.

Spreading rate: --

Processing instructions

	Colour colourless					
	Mixing ratio					
	Hardener		by weight (lacquer : hardener)		by volume (lacquer : hardener)	
	--	--	--	--	--	--
	Hardener					
	for complete paintwork				for partial paintwork	
	--	--	--	--	--	--
	Pot life					
	--	--	--	--	--	--
	Thinner					
	--	--	--	--	--	--
	Spray viscosity					
	gravity spray gun				Airmix/Airless	
	--	--	--	--	--	--
	Application mode					
	Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
	--	--	--	--	--	--
	Flash-off time					
	--	--	--	--	--	--
	Dry coat thickness					
	--	--	--	--	--	--
	Drying time					
	object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
	--	--	--	--	--	--

Note

- Storage:** at least 4 years in unopened original containers.
- VOC Regulation :** EU limit value for this product (category B/a): 850 g/l
This product contains max. 743 g/l of VOC.
- Processing conditions:** from +10 °C and up to 80 % relative humidity. Ensure adequate air ventilation.
- Processing instructions:** –